

**Product:** AGAT POS LED 2600 MICRO-PRM E 34 830 / 1200X300

**Index:** 19.4007.5211.34



## Description

Luminary body made from steel sheet powder coated in white. Luminary adapted to be mounted in 600x600 module ceilings and with adaptive frame in plasterboard ceilings. It is equipped with highly efficient LED sources of the newest lighting generation, with the average durability of 100000 h. Diffuser is made from polymethyl methacrylate with micro prism structure (micro prism part of diffuser is the outer side of the luminary). Luminary resistant to solids, dust, and liquids penetration (IP20).

## Product information

Category	<b>Recessed luminaires</b>
Family	<b>AGAT POS LED</b>
Name	<b>AGAT POS LED 2600 MICRO-PRM E 34 830 / 1200X300</b>
Index	<b>19.4007.5211.34</b>



## Light and electrical data


Light source	<b>LED</b>
Luminous flux LED [lm]	<b>2538</b>
LED power [W]	<b>12,4</b>
Luminaire luminous flux [lm]	<b>2081</b>
Power of luminaire [W]	<b>13,9</b>
Luminaire's light efficiency [lm/W]	<b>149,7</b>
Color of the light [K]	<b>3000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 76° / 89,4°</b>
Photobiological risk class (IEC/EN 62471)	<b>RG0</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP20/44</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>100000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>5 ÷ 30</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>46 (B10), 74 (B16), 72 (C10), 115 (C16)</b>

Mechanical data



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1196 x 296 x 55

A graph of light



Accessories

Index	01ARNL-AGK120X30
Name	Adaptive frame for plasterboard ceiling / 1200X300

