

Product: AGAT SLIM LED COMPACT 6000 PLX E 34 830 / L-600

Index: 19.4008.3A11.34



Description

Luminary made from powder coated steel sheet. Highly efficient and power saving LED solutions have been used here. The product may be equipped with PMMA opal diffuser or micro prism diffuser. Luminary dedicated for module ceilings, recommended to be used in public sectors such as offices, or conference rooms.

Product information

Category	Compact
Family	AGAT SLIM LED COMPACT
Name	AGAT SLIM LED COMPACT 6000 PLX E 34 830 / L-600
Index	19.4008.3A11.34
EAN	5902107855789















Light and electrical data

Light source	LED
Luminous flux LED [lm]	6016,3
LED power [W]	34,3
Luminaire luminous flux [lm]	4636
Power of luminaire [W]	38,4
Luminaire's light efficiency [lm/W]	120,7
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 101° / 103,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	80000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	atandard an/aff (E)
Driver	standard on/off (E)
Power factor cos φ	>0,95



Mechanical data		Assembly	mounted in module ceilings
	□⊒:H B	Material	steel sheet
Α		Color	RAL 9016 (white)
1		Diffuser	PLX (PMMA opal)
		Impact resistant	IK04
		Dimensions [mm]	596 x 115 x 88

A graph of light







