

Product: AGAT SLIM LED COMPACT 4000 PLX EDD 34 830 / L-600

Index: 19.4008.3B13.34



## **Description**

Luminary made from powder coated steel sheet. Highly efficient and power saving LED solutions have been used here. The product may be equipped with PMMA opal diffuser or micro prism diffuser. Luminary dedicated for module ceilings, recommended to be used in public sectors such as offices, or conference rooms.

## **Product information**

Category	Compact
Family	AGAT SLIM LED COMPACT
Name	AGAT SLIM LED COMPACT 4000 PLX EDD 34 830 / L-600
Index	19.4008.3B13.34
EAN	5902107355470















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	4446
LED power [W]	24
Luminaire luminous flux [lm]	3426
Power of luminaire [W]	26,9
Luminaire's light efficiency [lm/W]	127,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 101° / 103,2°
Dhatabialagical rial along (IEC/EN	200
Photobiological risk class (IEC/EN 62471)	RG0
ŭ (	I I
62471)	
62471) Protection against electric shock	1
Protection against electric shock Protection degree	I IP20/44
Protection against electric shock Protection degree Voltage	I IP20/44 220240 V, 5060 Hz
Protection against electric shock Protection degree  Voltage  Lifetime of LED sources [h]	I IP20/44 220240 V, 5060 Hz 80000
Protection against electric shock Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By	I IP20/44 220240 V, 5060 Hz 80000 L80/B10
Protection against electric shock Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By  Operating temperature range [°C]	I IP20/44 220240 V, 5060 Hz 80000 L80/B10 5 ÷ 30



Mechanical data		Assembly	mounted in module ceilings
	П□‡Н	Material	steel sheet
Α	B	Color	RAL 9016 (white)
		Diffuser	PLX (PMMA opal)
		Impact resistant	IK04
		Weight [kg]	1,64
		Dimensions [mm]	596 x 115 x 88

## A graph of light

