

Product: ARTSHAPE OVAL LED MEDIUM FULL-S SUSPENDED 11900 PLX EDD 21 840 / L-1585MM S-1,5M Index: 19.4011.2223.21




Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information	Category Are	chitectural luminaires	
	Family AR		
	Index 19		
	EAN 59	02107344801	
Light and electrical data	Light source		LED
	Luminous flux		13771,3
	LED power [V		81,2
		ninous flux [lm]	7298,8
	Power of lum		91
		ght efficiency [lm/W]	80,2
	Color of the li		4000
	CRI		>80
	SDCM (LED S	sources)	3
	Beam angle [110
		al risk class (IEC/EN 62471)) RG0
	Protection ag	ainst electric shock	I
	Protection de	gree	IP40
	Voltage		220240 V, 5060 Hz
	Lifetime of LE	ED sources [h]	100000
	Lx/By		L80/B10
	Operating ter	mperature range [°C]	5 ÷ 30
	Driver		DIM DALI (EDD)
	Power factor	cos φ	0,95
	Circuit load ca	apacity	7 (B10), 11 (B16), 11 (C10), 12 (C16



Mechanical data



T I	
	1500
	_

Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9006 (grey, metallic, fine structure)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	4,95
Dimensions [mm]	1585 x 230 x 85

