

Product: ARTSHAPE ROUND LED SMALL EDGE SUSPENDED 6000 PLX E 34 830 / S-1,5M

Index: 19.4012.1311.34



Description

Modernistic architectural luminaire in shapes of popular geometrical figures and fashionable design of simple form. The luminaire is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palette, the luminaires allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminaire is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. There is the possibility of fitting a luminaire with a sound-absorbing housing. On special request, it is possible to prepare an accessory (filling the centre with moss) on a fire-retardant board backing.

Product information

Category	Architectural luminaires
Family	ARTSHAPE ROUND LED
Name	ARTSHAPE ROUND LED SMALL EDGE SUSPENDED 6000 PLX E 34 830 / S-1,5M
Index	19.4012.1311.34
EAN	5902107177010



Light and electrical data


Light source	LED
Luminous flux LED [lm]	5681
LED power [W]	46
Luminaire luminous flux [lm]	2979
Power of luminaire [W]	50
Luminaire's light efficiency [lm/W]	59,6
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	0 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	5,45
Dimensions [mm]	Ø650 x 85

A graph of light



Accessories

Index 19.3272.0429.34

Name SUSPENSION NEW TYPE-J 34
LENGHT 1,5M WIRE 3X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E
LENGHT-1,5 METER WITHOUT
WIRE 1-POINT



Index 19.4012.1002.00

Name ARTSHAPE ROUND LED SMALL
EDGE SUSPENDED SOUND
ABSORBENT BLUE




Index 19.4012.1003.00

Name ARTSHAPE ROUND LED SMALL
EDGE SUSPENDED SOUND
ABSORBENT GREY



Index 19.4012.1001.00

Name ARTSHAPE ROUND LED SMALL
EDGE SUSPENDED SOUND
ABSORBENT RED



Index 19.4012.1007.00

Name ARTSHAPE ROUND LED SMALL
EDGE SUSPENDED SOUND
ABSORBENT VERSION-MOSS
LIGHT GREEN



Index 19.4012.1005.00

Name ARTSHAPE ROUND LED SMALL
EDGE SUSPENDED SOUND
ABSORBENT VERSION-S BLUE



Index 19.4012.1006.00

Name ARTSHAPE ROUND LED SMALL
EDGE SUSPENDED SOUND
ABSORBENT VERSION-S GREY



Index 19.4012.1004.00

Name ARTSHAPE ROUND LED SMALL
EDGE SUSPENDED SOUND
ABSORBENT VERSION-S RED

