

Product: ARTSHAPE ROUND LED SMALL FULL SUSPENDED 9000 PLX E 34 840 / S-1,5M Index: 19.4013.1421.34




Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.


Product information Category Architectural luminaires Family ARTSHAPE ROUND LED Name ARTSHAPE ROUND LED SMALL FULL SUR 840 / S-1,5M Index 19.4013.1421.34 EAN 5902107188641 Light and electrical data Light source LED Luminous flux LED [Im] 9406 LED power [W] 67 Luminaire luminous flux [Im] 6917 Power of luminaire [W] 74 Luminaire's light efficiency [Im/W] 93,5 Color of the light [K] 4000 CRI >80	
Name ARTSHAPE ROUND LED SMALL FULL SUB 840 / S-1,5M Index 19.4013.1421.34 EAN 5902107188641 Light and electrical data Light source LED Luminous flux LED [Im] 9406 LED power [W] 67 Luminaire luminous flux LED [Im] 6917 Power of luminaire [W] 74 Luminaire's light efficiency [Im/W] 93,5 Color of the light [K] 4000 CRI >80	
840 / S-1,5M Index 19.4013.1421.34 EAN 5902107188641 Image: Second Sec	
EAN5902107188641Image: Second stateImage: Second stateLight and electrical dataLight sourceLight sourceLEDLuminous flux LED [Im]9406LED power [W]67Luminaire luminous flux [Im]6917Power of luminaire [W]74Luminaire's light efficiency [Im/W]93,5Color of the light [K]4000CRI>80	
Light and electrical data Light source LED Luminous flux LED [Im] 9406 LED power [W] 67 Luminaire luminous flux [Im] 6917 Power of luminaire [W] 74 Luminaire's light efficiency [Im/W] 93,5 Color of the light [K] 4000 CRI >80	
Light and electrical dataLight sourceLEDLuminous flux LED [lm]9406LED power [W]67Luminaire luminous flux [lm]6917Power of luminaire [W]74Luminaire's light efficiency [lm/W]93,5Color of the light [K]4000CRI>80	
Luminous flux LED [Im]9406LED power [W]67Luminaire luminous flux [Im]6917Power of luminaire [W]74Luminaire's light efficiency [Im/W]93,5Color of the light [K]4000CRI>80	
Luminous flux LED [Im] 9406 LED power [W] 67 Luminaire luminous flux [Im] 6917 Power of luminaire [W] 74 Luminaire's light efficiency [Im/W] 93,5 Color of the light [K] 4000 CRI >80	
LED power [W]67Luminaire luminous flux [Im]6917Power of luminaire [W]74Luminaire's light efficiency [Im/W]93,5Color of the light [K]4000CRI>80	
Luminaire luminous flux [Im]6917Power of luminaire [W]74Luminaire's light efficiency [Im/W]93,5Color of the light [K]4000CRI>80	
Power of luminaire [W]74Luminaire's light efficiency [Im/W]93,5Color of the light [K]4000CRI>80	
Luminaire's light efficiency [lm/W]93,5Color of the light [K]4000CRI>80	
Color of the light [K] 4000 CRI >80	
SDCM (LED sources) 3	
Beam angle [°] (C0-C180) / (0 114,2°	90-C270) - 111,2° /
Photobiological risk class (IEC/EN RG0 62471)	
Protection against electric shock	
Protection degree IP20	
Voltage 220240 V, 50	60 Hz
Lifetime of LED sources [h] 100000	
Lx/By L80/B10	
Operating temperature range [°C] 0 ÷ 30	
Driver standard on/	off (E)
Power factor cos φ >0,95	
Circuit load capacity 9 (B10), 15 (E	

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	5,94
Dimensions [mm]	Ø650 x 85

A graph of light



Accessories

Index 6E1-5000KW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

