

# Product: ARTSHAPE ROUND LED MEDIUM EDGE UP&DOWN 4200/9000 PLX E 34 840 / S-1,5M Index: 19.4014.2221.34




## Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information	Category Architectural luminaires
	Family ARTSHAPE ROUND LED
	Name ARTSHAPE ROUND LED MEDIUM EDGE UP&DOWN 4200/9000 PLX
	E 34 840 / S-1,5M
	Index 19.4014.2221.34
	EAN 5902107225018
	$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c c c } \hline \begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c c c c } \hline \begin{tabular}{ c c c c c c c c c c c c c c c c c c c$
Light and electrical data	Light source LED
	Luminous flux LED [lm] 4256/8910
	LED power [W] 32/64
	Luminaire luminous flux [lm] 8449
	Power of luminaire [W] 106
	Luminaire's light efficiency [lm/W] 79,7
	Color of the light [K] 4000
	CRI >80
	Beam angle [°] (C0-C180) / (C90-C270) - 113,4° / 111,8°
	Protection against electric shock I
	Protection degree IP40
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] 100000
	Lx/By <b>L80/B10</b>
	Operating temperature range [°C] 0 ÷ 30
	Driver standard on/off (E)
	Power factor $\cos \varphi$ >0,95
	Circuit load capacity 5 (B10), 7 (B16), 8 (C10), 12 (C16)
Mechanical data	Assembly surface mounted on slings
	Material aluminum
	Color RAL 9016 (white)
	Diffuser PLX (PMMA opal)
	Impact resistant IK04
	Weight [kg] 7,7
	Dimensions [mm] Ø900 x 85

# A graph of light



## Accessories

#### Index 6E1-5000KW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

