

# Product: ARTSHAPE THREE LED MEDIUM EDGE SUSPENDED 4500 PLX E 34 830 / S-1,5M Index: 19.4020.2211.34




#### Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.


Product information	Category Architectural luminaires	
	Family ARTSHAPE THREE LED	
	Name ARTSHAPE THREE LED MEDIUM EDGE SUSPENDED 4500 P	
	34 830 / S-1,5M	
	Index 19.4020.2211.34	
	EAN <b>5902107199555</b>	
	$\overbrace{ED} (E) (E) (E) (E) (E) (E) (E) (E) (E) (E)$	Ŕ
Light and electrical data	Light source LED	
	Luminous flux LED [Im] 4262	
	LED power [W] 32	
	Luminaire luminous flux [Im] 2235	
	Power of luminaire [W] 35	
	Luminaire's light efficiency [lm/W] 63,9	
	Color of the light [K] <b>3000</b>	
	CRI >80	
	SDCM (LED sources) 3	
	Beam angle [°] (C0-C180) / (C90-C270) - 113,4° 111,8°	° I
	Photobiological risk class (IEC/EN <b>RG0</b> 62471)	
	Protection against electric shock	
	Protection degree IP40	
	Voltage 220240 V, 5060 Hz	
	Lifetime of LED sources [h] 100000	
	Lx/By <b>L80/B10</b>	
	Operating temperature range [°C] 0 ÷ 30	
	Driver standard on/off (E)	
	Power factor cos φ >0,95	
	Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54	(C16)

### **Mechanical data**



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	900 x 809 x 85

## A graph of light



#### Accessories

Index 6E1-5000KW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

