

Product: ARTSHAPE THREE LED MEDIUM EDGE SUSPENDED 9000 PLX EDD 34 840 / S-1,5M Index: 19.4020.2423.34




Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.


Product information	C	Category Architectural luminaires
		amily ARTSHAPE THREE LED
	Ν	Name ARTSHAPE THREE LED MEDIUM EDGE SUSPENDED 9000 PLX EDD 34 840 / S-1,5M
	Ir	ndex 19.4020.2423.34
	E	EAN 5902107176532
		$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c c c c } \hline \begin{tabular}{ c c c c c c c c c c c c c c c c c c c$
Light and electrical data		Light source LED
		Luminous flux LED [Im] 8910
		LED power [W] 64
		Luminaire luminous flux [Im] 4672
		Power of luminaire [W] 70
		Luminaire's light efficiency [Im/W] 66,7
		Color of the light [K] 4000
	C	CRI >80
	S	SDCM (LED sources) 3
	В	Beam angle [°] (C0-C180) / (C90-C270) - 113,4° / 111,8°
		Photobiological risk class (IEC/EN RG0 52471)
	P	Protection against electric shock
	P	Protection degree IP40
	V	/oltage 220240 V, 5060 Hz
	L	Lifetime of LED sources [h] 100000
	L	_x/By L80/B10
	C	Dperating temperature range [°C] 0 ÷ 30
	D	Driver DIM DALI (EDD)
	P	Power factor cos φ >0,95
	C	Circuit load capacity 8 (B10), 13 (B16), 13 (C10), 21 (C16)

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	900 x 809 x 85

A graph of light



Accessories

Index 6E1-500OKW1P-5

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 5X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

