

Product: AGAT CLEAN-ECO LED 8800 PLX EDD IP65 34 840 / 600X600

Index: 19.4024.2223.34



Description

Luminary designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

Category	Clean luminaires - recessed
Family	AGAT CLEAN-ECO LED
Name	AGAT CLEAN-ECO LED 8800 PLX EDD IP65 34 840 / 600X600
Index	19.4024.2223.34
EAN	5902107262570
















Light and electrical data

Light source	LED	
Luminous flux LED [lm]	9130	
LED power [W]	46,8	
Luminaire luminous flux [lm]	6707	
Power of luminaire [W]	49,1	
Luminaire's light efficiency [lm/W]	136,6	
Color of the light [K]	4000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000 (1) / 147000 (2)	
Lx/By	L80/B10 (1) / L70/B50 (2)	
Operating temperature range [°C]	5 ÷ 30	
	DIM DALL/EDD)	
Driver	DIM DALI (EDD)	
Driver Power factor cos φ	>0,95	




$\mathbf{n} / \mathbf{n} \sim \mathbf{n}$	10 D	\sim	Aloto.
MIC -	пап		Hala
IVICC		Juli	data



Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	595 x 595 x 75

A graph of light





Accessories

Index 2C1A7392

Name Adaptive frame for plasterboard ceiling (600x600)

