

Product: AGAT CLEAN-ECO LED 12000 PLX E IP65 34 840 / 600X600

Index: 19.4024.2321.34



Description

Luminary designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

Category	Clean luminaires - recessed
Family	AGAT CLEAN-ECO LED
Name	AGAT CLEAN-ECO LED 12000 PLX E IP65 34 840 / 600X600
Index	19.4024.2321.34
EAN	5902107263485
















Light and electrical data

Linkt course	1.50		
Light source	LED		
Luminous flux LED [lm]	12495		
LED power [W]	77		
Luminaire luminous flux [lm]	9179		
Power of luminaire [W]	86		
Luminaire's light efficiency [lm/W]	106,7		
Color of the light [K]	4000		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP65		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	100000 (1) / 147000 (2)		
Lx/By	L80/B10 (1) / L70/B50 (2)		
Operating temperature range [°C]	5 ÷ 30		
Driver	standard on/off (E)		
2			
Power factor cos φ	>0,95		




	h 0h		20+2
MA			11212
IVIC	, i icu i	-Cai	data



Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	6,6
Dimensions [mm]	595 x 595 x 75

A graph of light





Accessories

Index 2C1A7392

Name Adaptive frame for plasterboard ceiling (600x600)

