

Product: AGAT CLEAN LED 8800 SHM EDD IP65 34 827-865 / 600X600 TUNABLE WHITE

Index: 19.4026.3553.34



Description

Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame. Luminary recommended for: emergency departments, intensive care units, and treatment rooms. *Selected luminary variants are available with ENEC certificate.

Product information

Category	Clean luminaires - recessed
Family	AGAT CLEAN LED
Name	AGAT CLEAN LED 8800 SHM EDD IP65 34 827-865 / 600X600 TUNABLE WHITE
Index	19.4026.3553.34
EAN	5902107195458
















Light and electrical data

Light source	LED	
Luminous flux LED [lm]	8608÷9148 (2700÷6500 K)	
LED power [W]	54÷57 (6500÷2700 K)	
Luminaire luminous flux [lm]	6929÷7363 (2700÷6500 K)	
Power of luminaire [W]	60÷64 (6500÷2700 K)	
Luminaire's light efficiency [lm/W]	108÷123 (2700÷6500 K)	
Color of the light [K]	2700 ÷ 6500	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN	RG0	
62471)		
62471) Protection against electric shock	1	
	I IP65	
Protection against electric shock	•	
Protection against electric shock Protection degree	IP65	
Protection against electric shock Protection degree Voltage	IP65 220240 V, 5060 Hz	
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h]	IP65 220240 V, 5060 Hz 50000	
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP65 220240 V, 5060 Hz 50000 L80/B10	
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP65 220240 V, 5060 Hz 50000 L80/B10 5 ÷ 30	




Mec	hani	001	data.
IVIE	папп	Call	пата
11100		Ou:	uucu



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	596 x 596 x 76
Mounting hole [mm]	580 x 580

A graph of light



Accessories

Index 2M-X414LKPIPT5

Name Mounting clips set for plasterboard ceiling

