

Product: BERYL NEW LED K-2 1800 MICRO-PRM EDD IP20/44 33 827-865

Index: 19.4030.5153.33



### **Description**

Aluminum cast housing. This technology significantly increases possibility of application of particular luminaire due to lower ceiling load since additional cooling radiator is not required. Beryl New LED K has higher efficiency and efficiency than the previous version. Luminaire is dedicated for prestigious interiors such as hotels, banks and offices of higher standard. Owing to the newest components and renowned producers of LEDs applied it was possible to build such luminaires which save energy consumption comparing with traditional solutions. LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K. The luminaire has the ability to adjust the optics in two planes (in the vertical axis by 359° and to the left and right 15°). Note: the color of the frame and housing has a slightly different shade than the color of the inner reflector cover.

### **Product information**

| Category | Recessed luminaires                                     |
|----------|---|
| Family   | BERYL NEW LED K   |
| Name     | BERYL NEW LED K-2 1800 MICRO-PRM EDD IP20/44 33 827-865 |
| Index    | 19.4030.5153.33   |
| EAN      | 5902107199432   |

















## Light and electrical data

| Light source                        | LED                                     |
|-------------------------------------|---|
| Luminous flux LED [lm]              | 1942÷1995 (2450÷7000)                   |
| LED power [W]                       | 14                                      |
| Luminaire luminous flux [lm]        | 1335÷1372 (2450÷7000)                   |
| Power of luminaire [W]              | 16                                      |
| Luminaire's light efficiency [lm/W] | 83÷86 (2450÷7000)                       |
| Color of the light [K]              | 2450 ÷ 7000                             |
| CRI                                 | >85                                     |
| SDCM (LED sources)                  | 2                                       |
| Beam angle [°]                      | (C0-C180) / (C90-C270) - 79,4° / 77,4°  |
| Protection against electric shock   | II                                      |
| Protection degree                   | IP20/44                                 |
| Voltage                             | 220240 V, 5060 Hz                       |
| Lifetime of LED sources [h]         | 95000 (1) / 100000 (2) / 100000 (3)     |
| Lx/By                               | L90/B10 (1) / L80/B10 (2) / L70/B10 (3) |
| Operating temperature range [°C]    | 5 ÷ 30                                  |
| Driver                              | DIM DALI (EDD)                          |
| Power factor cos φ                  | >0,95                                   |
| Circuit load capacity               | 27 (B10), 43 (B16), 43 (C10), 73 (C16)  |

#### Mechanical data





| Assembly           | mounted in module ceilings, as well as plasterboard ceilings |
|--------------------|--|
| Material           | aluminum   |
| Color              | RAL 9010 (white)   |
| Diffuser           | Micro-PRM (micro-prismatic diffuser PMMA)                    |
| Impact resistant   | IK04   |
| Weight [kg]        | 1,2  |
| Dimensions [mm]    | 160 x 160 x 136  |
| Mounting hole [mm] | 148 x 148  |



# A graph of light

