

**Product:** BERYL NEW LED O-2 1800 MICRO-PRM EDD IP20/44 33 827-865

**Index:** 19.4034.5153.33



## Description

Aluminum cast housing. This technology significantly increases possibility of application of particular luminaire due to lower ceiling load since additional cooling radiator is not required. Luminaire is dedicated for prestigious interiors such as hotels, banks and offices of higher standard. Owing to the newest components and renowned producers of LEDs applied it was possible to build such luminaires which save energy consumption comparing with traditional solutions. LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K.

## Product information

Category	Recessed luminaires
Family	BERYL NEW LED O IP20/44
Name	BERYL NEW LED O-2 1800 MICRO-PRM EDD IP20/44 33 827-865
Index	19.4034.5153.33
EAN	5902107199319



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	1942÷1995 (2450÷7000)
LED power [W]	14
Luminaire luminous flux [lm]	1292÷1328 (2450÷7000)
Power of luminaire [W]	16
Luminaire's light efficiency [lm/W]	81÷83 (2450÷7000)
Color of the light [K]	2450 ÷ 7000
CRI	>85
Beam angle [°]	(C0-C180) / (C90-C270) - 113,2° / 110,8°
Protection against electric shock	II
Protection degree	IP20/44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	95000 (1) / 100000 (2) / 100000 (3)
Lx/By	L90/B10 (1) / L80/B10 (2) / L70/B10 (3)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	27 (B10), 43 (B16), 43 (C10), 73 (C16)

## Mechanical data



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	aluminum
Color	RAL 9010 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	Ø165 x 100
Mounting hole [mm]	Ø140

A graph of light

