

Product: BERYL NEW LED O-1 1800 PLX E 33 IP20/44 830

Index: 19.4034.3111.33



Description

Aluminum cast housing. This technology significantly increases possibility of application of particular luminaire due to lower ceiling load since additional cooling radiator is not required. Luminaire is dedicated for prestigious interiors such as hotels, banks and offices of higher standard. Owing to the newest components and renowned producers of LEDs applied it was possible to build such luminaires which save energy consumption comparing with traditional solutions.

Product information

| | |
|----------|---|
| Category | Recessed luminaires |
| Family | BERYL NEW LED O IP20/44 |
| Name | BERYL NEW LED O-1 1800 PLX E 33 IP20/44 830 |
| Index | 19.4034.3111.33 |
| EAN | 5902107151232 |



Light and electrical data

| | |
|---|--|
| Light source | LED |
| Luminous flux LED [lm] | 2000 |
| LED power [W] | 11,3 |
| Luminaire luminous flux [lm] | 1318 |
| Power of luminaire [W] | 12,8 |
| Luminaire's light efficiency [lm/W] | 103 |
| Color of the light [K] | 3000 |
| CRI | 85 |
| SDCM (LED sources) | 2 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 81,6° / 81,6° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | II |
| Protection degree | IP20/44 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 83000 (1) / 100000 (2) / 100000 (3) |
| Lx/By | L90/B10 (1) / L80/B10 (2) / L70/B10 (3) |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 61 (B10), 98 (B16), 102 (C10), 164 (C16) |

Mechanical data



| | |
|--------------------|--|
| Assembly | mounted in module ceilings, as well as plasterboard ceilings |
| Material | aluminum |
| Color | RAL 9010 (white) |
| Diffuser | PLX (PMMA opal) |
| Impact resistant | IK04 |
| Weight [kg] | 0,23 |
| Dimensions [mm] | Ø100 x 75 |
| Mounting hole [mm] | Ø85 |

A graph of light

