

Product: BERYL NEW LED O-1 1800 PLX E 33 IP20/65 830

Index: 19.4036.3111.33



Description

Aluminum cast housing. This technology significantly increases possibility of application of particular luminaire due to lower ceiling load since additional cooling radiator is not required. Luminaire is dedicated for prestigious interiors such as hotels, banks and offices of higher standard. Owing to the newest components and renowned producers of LEDs applied it was possible to build such luminaires which save energy consumption comparing with traditional solutions.

Product information

Category	Recessed luminaires	
Family	BERYL NEW LED O IP20/65	
Name	BERYL NEW LED O-1 1800 PLX E 33 IP20/65 830	
Index	19.4036.3111.33	
EAN	5902107170691	







Light and electrical data

Light source	LED
Luminous flux LED [lm]	2000
LED power [W]	11,3
Luminaire luminous flux [lm]	1318
Power of luminaire [W]	12,8
Luminaire's light efficiency [lm/W]	103
Color of the light [K]	3000
CRI	85
SDCM (LED sources)	2
Beam angle [°]	(C0-C180) / (C90-C270) - 81,6° / 81,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20/65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	83000 (1) / 100000 (2) / 100000 (3)
Lx/By	L90/B10 (1) / L80/B10 (2) / L70/B10 (3)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Dilvei	Staridard Official (L)
Power factor cos φ	>0,95



Mechanical data	Assembly	mounted in module ceilings, as well as plasterboard ceilings
	Material	aluminum
	Color	RAL 9010 (white)
	Diffuser	PLX (PMMA opal)
	Impact resistant	IK04
	Weight [kg]	0,24
	Dimensions [mm]	Ø100 x 75
	Mounting hole [mm]	Ø85

A graph of light

