

Product: X-LINE SLIM RECESSED LOW UGR LED 4200 RASTER DAISY-BLACK-WIDE E 21 840 / L-1146MM

Index: 19.4152.3321.21



Description

Luminaire made of aluminium profile. Compared to traditional X-Line G/K LED, the size has been reduced and the structure enclosed in a narrower profile, which allows a more elegant aspect of the product. X-Line Slim Recessed uses an antiglare louvre. All this makes it possible to adjust light and create lighting systems, easing the creation of a comfortable view of indoor spaces and their aesthetics. X-Line Slim Recessed is designed for built-in installation on ceilings.

Product information

Category	Recessed luminaires
Family	X-LINE SLIM RECESSED LOW UGR LED
Name	X-LINE SLIM RECESSED LOW UGR LED 4200 RASTER DAISY-BLACK-WIDE E 21 840 / L-1146MM
Index	19.4152.3321.21
EAN	5902107556068















Light and electrical data

Light source	LED		
Luminous flux LED [lm]	4432		
LED power [W]	22,4		
Luminaire luminous flux [lm]	3678,6		
Power of luminaire [W]	25,5		
Luminaire's light efficiency [lm/W]	144,3		
Color of the light [K]	4000		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP40		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [b]	100000		
Lifetime of LED sources [h]	100000		
Lx/By	100000 L80/B10		
Lx/By	L80/B10		
Lx/By Operating temperature range [°C]	L80/B10 5 ÷ 35		



		-			
$\mathbf{R} / \mathbf{I} \wedge$	nh.	2 IZ	221	dat	-
IVIE	• • • • •	41 II		uai	





Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	RAL 9006 (grey)
Diffuser	RASTER (anti-glare louver)
Impact resistant	IK04
Dimensions [mm]	1146 x 70 x 75
Mounting hole [mm]	1136 x 55

A graph of light







