

**Product:** X-LINE SLIM RECESSED LOW UGR LED 5250 RASTER DAISY-BLACK-WIDE E 34 830 LINE-S / L-1401MM

**Index:** 19.4154.6311.34



## Description

Luminaire made of aluminium profile. Compared to traditional X-Line G/K LED, the size has been reduced and the structure enclosed in a narrower profile, which allows a more elegant aspect of the product. X-Line Slim Recessed uses an anti-glare louvre. All this makes it possible to adjust light and create lighting systems, easing the creation of a comfortable view of indoor spaces and their aesthetics. X-Line Slim Recessed is designed for built-in installation on ceilings. The luminaires are adjusted to be linked together with specially designed connectors, which provide great freedom in arranging elements of the system as well as great functionality.

## Product information

|          |   |
|----------|---|
| Category | <b>Recessed luminaires</b>  |
| Family   | <b>X-LINE SLIM RECESSED LOW UGR LED LINE</b>  |
| Name     | <b>X-LINE SLIM RECESSED LOW UGR LED 5250 RASTER DAISY-BLACK-WIDE E 34 830 LINE-S / L-1401MM</b> |
| Index    | <b>19.4154.6311.34</b>  |



## Light and electrical data

|   |   |
|---|---|
| Light source                              | <b>LED</b>                                    |
| Luminous flux LED [lm]                    | <b>5265</b>                                   |
| LED power [W]                             | <b>28</b>                                     |
| Luminaire luminous flux [lm]              | <b>4370</b>                                   |
| Power of luminaire [W]                    | <b>31,8</b>                                   |
| Luminaire's light efficiency [lm/W]       | <b>137,4</b>                                  |
| Color of the light [K]                    | <b>3000</b>                                   |
| CRI                                       | <b>&gt;80</b>                                 |
| SDCM (LED sources)                        | <b>3</b>                                      |
| Beam angle [°]                            | <b>(C0-C180) / (C90-C270) - 72,6° / 74,4°</b> |
| Photobiological risk class (IEC/EN 62471) | <b>RG0</b>                                    |
| Protection against electric shock         | <b>I</b>                                      |
| Protection degree                         | <b>IP40</b>                                   |
| Voltage                                   | <b>220..240 V, 50..60 Hz</b>                  |
| Lifetime of LED sources [h]               | <b>100000</b>                                 |
| Lx/By                                     | <b>L80/B10</b>                                |
| Operating temperature range [°C]          | <b>5 ÷ 35</b>                                 |
| Driver                                    | <b>standard on/off (E)</b>                    |
| Power factor cos φ                        | <b>&gt;0,95</b>                               |
| Circuit load capacity                     | <b>19 (B10), 30 (B16), 31 (C10), 50 (C16)</b> |

**Mechanical data**



|                    |   |
|--------------------|---|
| Assembly           | <b>mounted in plasterboard ceilings</b> |
| Material           | <b>aluminum</b>                         |
| Color              | <b>RAL 9016 (white)</b>                 |
| Diffuser           | <b>RASTER (anti-glare louvre)</b>       |
| Impact resistant   | <b>IK04</b>                             |
| Dimensions [mm]    | <b>1401 x 70 x 75</b>                   |
| Mounting hole [mm] | <b>1401 x 55</b>                        |

**A graph of light**

