

**Product:** X-LINE SLIM RECESSED LOW UGR LED 5250 RASTER DAISY-BLACK-WIDE E 34 840 LINE-EP / L-1413MM

**Index:** 19.4155.9321.34



## Description

Luminaire made of aluminium profile. Compared to traditional X-Line G/K LED, the size has been reduced and the structure enclosed in a narrower profile, which allows a more elegant aspect of the product. X-Line Slim Recessed uses an anti-glare louvre. All this makes it possible to adjust light and create lighting systems, easing the creation of a comfortable view of indoor spaces and their aesthetics. X-Line Slim Recessed is designed for built-in installation on ceilings. The luminaires are adjusted to be linked together with specially designed connectors, which provide great freedom in arranging elements of the system as well as great functionality. \*Selected luminary variants are available with ENEC certificate.

## Product information

Category	Recessed luminaires
Family	X-LINE SLIM RECESSED LOW UGR LED LINE
Name	X-LINE SLIM RECESSED LOW UGR LED 5250 RASTER DAISY-BLACK-WIDE E 34 840 LINE-EP / L-1413MM
Index	19.4155.9321.34
EAN	5902107293338



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	5540
LED power [W]	28
Luminaire luminous flux [lm]	4598,2
Power of luminaire [W]	31,8
Luminaire's light efficiency [lm/W]	144,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	19 (B10), 30 (B16), 31 (C10), 50 (C16)

**Mechanical data**



Assembly	<b>mounted in plasterboard ceilings</b>
Material	<b>aluminum</b>
Color	<b>RAL 9016 (white)</b>
Diffuser	<b>RASTER (anti-glare louver)</b>
Impact resistant	<b>IK04</b>
Dimensions [mm]	<b>1413 x 70 x 75</b>
Mounting hole [mm]	<b>1408 x 55</b>

**A graph of light**

