

Product: A 220000

1133MM

Index: 19.4156.2353.34



Description

Luminaire made of aluminium profile. Compared to traditional X-Line G/K LED, the size has been reduced and the structure enclosed in a narrower profile, which allows a more elegant aspect of the product. X-Line Slim Recessed uses an antiglare louvre. All this makes it possible to adjust light and create lighting systems, easing the creation of a comfortable view of indoor spaces and their aesthetics. X-Line Slim Recessed is designed for built-in installation on ceilings. The luminaries are adjusted to be linked together with specially designed connectors, which provide great freedom in arranging elements of the system as well as great functionality. The luminaire is equipped with LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K.

Product information

Category	Recessed luminaires		
Family	X-LINE SLIM RECESSED LOW UGR LED LINE		
Name	X-LINE SLIM RECESSED LOW UGR LED 4200 RASTER DAISY- BLACK-WIDE EDD 34 827-865 LINE-1EL / L-1133MM		
Index	19.4156.2353.34		
EAN	5902107293253		















Light and electrical data

Light source	LED		
Luminous flux LED [lm]	3990÷4305 (2700÷6500 K)		
LED power [W]	22,8		
Luminaire luminous flux [lm]	3312÷3574 (2700÷6500 K)		
Power of luminaire [W]	25,6		
Luminaire's light efficiency [lm/W]	129÷140 (2700÷6500 K)		
Color of the light [K]	2700 ÷ 6500		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP40		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	50000		
Lx/By	L80/B10		
Operating temperature range [°C]	5 ÷ 35		
Driver	DIM DALI (EDD)		
Power factor cos φ	>0,95		
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)		



N/I	α	han	100	l data
IVI	C. (.)	пап	III (.al	ıuala





Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	RASTER (anti-glare louver)
Impact resistant	IK04
Dimensions [mm]	1133 x 70 x 75
Mounting hole [mm]	1128 x 55

A graph of light





