

#### Product: X-LINE LED 5200 PLX E 24 840 LINE-EP / L-2247MM Index: 19.4162.5121.24



### Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

### **Product information**

Category	Surface mounted luminaires
Family	X-LINE LED LINE
Name	X-LINE LED 5200 PLX E 24 840 LINE-EP / L-2247MM
Index	19.4162.5121.24
EAN	5902107088170
	$\overbrace{LED} \textcircled{\mathbb{E}} \textcircled{\mathbb{E}} \textcircled{\mathbb{E}} \textcircled{\mathbb{E}} \textcircled{\mathbb{E}} \textcircled{\mathbb{E}} \textcircled{\mathbb{E}} $

## Light and electrical data

Light source	LED
Luminous flux LED [lm]	5234
LED power [W]	26,6
Luminaire luminous flux [lm]	3489
Power of luminaire [W]	28,2
Luminaire's light efficiency [lm/W]	123,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109° / 107,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,95
Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16)




Mechanical data	∏‡н	Assembly	directly mounted to ceiling construction or surface mounted on slings
Α	∟ <u></u> *''  ++  B	Material	aluminum
la	U	Color	anodised aluminum
		Diffuser	PLX (PMMA opal)
		Impact resistant	IK04
		Weight [kg]	5,29
		Dimensions [mm]	2247 x 63 x 74
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 10° 10° 10° 10° 10° 10° 10° 10

# Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

