

**Product: X-LINE LED 3250 PLX E 24 830 LINE-EP / L-1407MM** 

Index: 19.4162.3111.24



## **Description**

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

### **Product information**

Category	Surface mounted luminaires
Family	X-LINE LED LINE
Name	X-LINE LED 3250 PLX E 24 830 LINE-EP / L-1407MM
Index	19.4162.3111.24
EAN	5901867400963













## Light and electrical data

Light source	LED
Luminous flux LED [lm]	3158
LED power [W]	17,1
Luminaire luminous flux [lm]	2105
Power of luminaire [W]	18,3
Luminaire's light efficiency [lm/W]	115
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109° / 107,2°
Photobiological risk class (IEC/EN 62471)	RG0
· · -/	
Protection against electric shock	1
,	I IP44
Protection against electric shock	•
Protection against electric shock Protection degree	IP44
Protection against electric shock Protection degree Voltage	IP44 220240 V, 5060 Hz
Protection against electric shock Protection degree  Voltage  Lifetime of LED sources [h]	IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2)
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2)
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 30



Mechanical data	Assembly	directly mounted to ceiling construction or surface mounted on slings
	Material	aluminum
	Color	anodised aluminum
	Diffuser	PLX (PMMA opal)
	Impact resistant	IK04
	Weight [kg]	3,4
	Dimensions [mm]	1407 x 63 x 74

# A graph of light





#### **Accessories**

Index 6E1-500KWAN1P-3

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 3X 1-POINT Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24
LENGHT 1,5M WITHOUT WIRE 1POINT

Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT Index 0E1XLL-SLED

Name X-LINE Clamp for line luminaires

