

Product: X-LINE LED 1300 MICRO-PRM EDD 24 830 LINE-1EL / L-567MM Index: 19.4164.1213.24



Description

Voltage

Lx/By

Driver

Lifetime of LED sources [h]

Power factor $\cos \phi$

Circuit load capacity

Operating temperature range [°C]

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Light and electrical data

	Family	X-LINE LED L	INE							
	Name	X-LINE LED 1300 MICRO-PRM EDD 24 830 LINE-1EL / L-567MM								
	Index	19.4164.1213	.24							
				E		P ₄₄	K ₀₄	Indoor		
	Light sour	rce		LE	ED					
	Luminous flux LED [lm]			13	849					
	LED power [W]			8						
	Luminaire	lumin <mark>ous flux [</mark>	[lm]	10	016					
	Power of luminaire [W]			9	9					
	Luminaire's light efficiency [lm/W]			11	112,9					
	Color of th	ne light [K]		30	000					
	CRI			>8	>80					
	SDCM (LED sources)			3	3					
	Beam angle [°]			(C	(C0-C180) / (C90-C270) - 82,8° / 97,2°					
	Photobiological risk class (IEC/EN 62471)			R	RG0					
	Protection against electric shock			I	I					
	Protection	n degree		IP	44					

220..240 V, 50..60 Hz

DIM DALI (EDD)

5 ÷ 30

>0,9

(C16)

100000 (1) / 147000 (2)

L80/B10 (1) / L70/B50 (2)

14 (B10), 24 (B16), 22 (C10), 36

Category Surface mounted luminaires



Mechanical data	□‡H B	Assembly	directly mounted to ceiling construction or surface mounted on slings			
Α		Material	aluminum			
	U	Color	anodised aluminum			
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)			
		Impact resistant	IK04			
		Weight [kg]	1,62			
		Dimensions [mm]	567 x 63 x 74			
			75° 60° 45° 45° 30° 30° 45° 40° 40° 40° 40° 40° 40° 40° 45° 45° 45° 45° 45° 45° 45° 45° 45° 45			

Accessories











Index 0E1XLL-SLED
Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 18-06-2025