

Product: X-LINE LED 2600 MICRO-PRM EDD 24 830 LINE-1EL / L-1127MM

Index: 19.4164.2213.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information

Category	Surface mounted luminaires
Family	X-LINE LED LINE
Name	X-LINE LED 2600 MICRO-PRM EDD 24 830 LINE-1EL / L-1127MM
Index	19.4164.2213.24
EAN	5902107074715















Light and electrical data

Light source	LED
Luminous flux LED [lm]	2525
LED power [W]	13,3
Luminaire luminous flux [lm]	1902
Power of luminaire [W]	14,4
Luminaire's light efficiency [lm/W]	132,1
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
Photobiological risk class (IEC/EN 62471)	RG0
Dueta etiana a main et alle etnis also els	1
Protection against electric shock	ı
Protection degree	IP44
	•
Protection degree	IP44
Protection degree Voltage	IP44 220240 V, 5060 Hz
Protection degree Voltage Lifetime of LED sources [h]	IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2)
Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2)
Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 30




١	Mechanical data	
ļ]



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	2,71
Dimensions [mm]	1127 x 63 x 74

A graph of light





Accessories


Index 6E1-500KWAN1P-5

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24
LENGHT 1,5M WITHOUT WIRE 1POINT




Index 0E1XLL-SLED

Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT

