

## Product: X-LINE LED 3900 MICRO-PRM EDD 24 840 LINE-1S / L-1682MM Index: 19.4166.4223.24



## Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product	information

Light and electrical data

Category	Surface mou	inted	lumin	aires					
Family	X-LINE LED	LINE							
Name	X-LINE LED	3900	MICRO	D-PRM	EDD 24	840 LIN	NE-1S/	L-16821	MM
Index	19.4166.4223	3.24							
	C	E	LED	E		$\mathbb{IP}_{44}$	<b>K</b> <sub>04</sub>	Indoor	
Light sour	се			L	ED				
Luminous	flux LED [lm]			3	926				
LED powe	er [W]			2	0				
Luminaire	luminous flux	[lm]		2	957				
Power of I	uminaire [W]			2	1,7				
Luminaire	's light efficien	cy [lm	n/W]	1	36,3				
	1. 1. 1. 1. 1.			-					

(C16)

Cotogon / Curfage manufad luminairea

Power of luminaire [W]	21,7
Luminaire's light efficiency [lm/W]	136,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41




Mechanical data	Птн	Assembly	directly mounted to ceiling construction or surface mounted on slings		
A	∟ <u>↓</u> ⊓  ++  B	Material	aluminum		
	D	Color	anodised aluminum		
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)		
		Impact resistant	IK04		
		Weight [kg]	4,1		
		Dimensions [mm]	1682 x 63 x 74		
			90° 75° 60° 60° 60° 60° 60° 60° 60° 60		

## Accessories












Index 0E1XLL-SLED
Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025