

## Product: X-LINE LED 6600 PLX E 24 840 LINE-EP / L-1687MM Index: 19.4168.4121.24



## Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information	
---------------------	--

Category	Surface mounted luminaires				
Family	X-LINE LED LINE				
Name	X-LINE LED 6600 PLX E 24 840 LINE-EP / L-1687MM 19.4168.4121.24				
Index					
	$\overbrace{LED} \textcircled{\ } @$ } \textcircled{\ } \textcircled{\ } \textcircled{\ } @ } \textcircled{\ } \textcircled{\ } @ } @				

## Light and electrical data

LED
6848
33,7
4565
35,3
129,3
4000
>80
3
(C0-C180) / (C90-C270) - 109° / 107,2°
RG0
I
IP44
220240 V, 5060 Hz
100000 (1) / 147000 (2)
L80/B10 (1) / L70/B50 (2)
5 ÷ 30
standard on/off (E)
>0,95
16 (B10), 25 (B16), 26(C10), 42 (C16)



	⊟tH B	Assembly	directly mounted to ceiling construction or surface mounted on slings aluminum	
Α		Material Color		
			anodised aluminum	
		Diffuser	PLX (PMMA opal)	
		Impact resistant	IK04	
		Weight [kg]	3,97	
		Dimensions [mm]	1687 x 63 x 74	
A graph of light			90° 75° 60° 45° 30° 15° 0° 120 45° 160 45° 30° 15° 0° 30° 15° 30°	

## Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT

Index 0E1XLL-SLED Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 18-06-2025