

Product: X-LINE LED 2200 MICRO-PRM E 24 840 LINE-EP / L-567MM Index: 19.4168.1221.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Ρ	r	O	d	ct	iı	'n	fa	r	n	1	a	ti	o	n	
				C I			•				α	u	U		

Category	ory Surface mounted luminaires									
Family	X-LINE LED LINE									
Name	X-LINE LED 2200 MICRO-PRM E 24 840 LINE-EP / L-567MM									
Index	19.4168.1221.24									
	$\underbrace{}_{\operatorname{ED}} \underbrace{}_{\operatorname{ED}} _{\operatorname{ED}} \operatorname$									

Light and electrical data

Light source	LED
Luminous flux LED [lm]	2283
LED power [W]	11,7
Luminaire luminous flux [lm]	1720
Power of luminaire [W]	12,6
Luminaire's light efficiency [lm/W]	136,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,9
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)



Mechanical data	Пїн	Assembly	directly mounted to ceiling construction or surface mounted on slings			
A A		Material	aluminum anodised aluminum			
l ₄ ∧ ∧		Color				
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)			
		Impact resistant	IK04			
		Weight [kg]	1,65			
		Dimensions [mm]	567 x 63 x 74			
			90° 75° 60° 45° 45° 45° 30° 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15° 15° 0° 15° 15° 15° 15° 15° 15° 15° 15			

Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT

Index 0E1XLL-SLED Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 18-06-2025