

## Product: X-LINE LED 4400 MICRO-PRM E 24 830 LINE-S / L-1122MM Index: 19.4169.2211.24



## Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Ρ	ra	bd	U	ct	ir	nf	or	m	ati	ioi	า
		Ju		υL					uu		

Category	Surface mounted luminaires
Family	X-LINE LED LINE
Name	X-LINE LED 4400 MICRO-PRM E 24 830 LINE-S / L-1122MM
Index	19.4169.2211.24
	$\underbrace{}_{\operatorname{ED}} \bigoplus _{\operatorname{ED}} \bigoplus _{\operatorname{P44}} _{\operatorname{F44}} \bigoplus _{\operatorname{F45}} \bigoplus _{$

## Light and electrical data

	Light source	LED		
	Luminous flux LED [lm]	4406		
	LED power [W]	23,4		
	Luminaire luminous flux [lm]	3319		
	Power of luminaire [W]	24,7		
	Luminaire's light efficiency [lm/W]	134,4		
	Color of the light [K]	3000		
	CRI	>80		
	SDCM (LED sources)	3		
	Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°		
	Photobiological risk class (IEC/EN 62471)	RG0		
	Protection against electric shock	I		
	Protection degree	IP44		
	Voltage	220240 V, 5060 Hz		
	Lifetime of LED sources [h]	100000 (1) / 147000 (2)		
	Lx/By	L80/B10 (1) / L70/B50 (2)		
	Operating temperature range [°C]	5 ÷ 30		
	Driver	standard on/off (E)		
	Power factor $\cos \phi$	>0,95		
	Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)		



Mechanical data	□ <u> </u> •	Assembly	directly mounted to ceiling construction or surface mounted on slings
. A	⊢ tH B	Material	aluminum
	D	Color	anodised aluminum
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Weight [kg]	2,88
		Dimensions [mm]	1122 x 63 x 74
A graph of light			$105^{\circ}$ $90^{\circ}$ $75^{\circ}$ $60^{\circ}$ $60^{\circ}$ $45^{\circ}$ 200 $45^{\circ}$ 200 $45^{\circ}$ 200 $45^{\circ}$ 200 $45^{\circ}$ 200 $40^{\circ}$ $15^{\circ}$ $0^{\circ}$ $15^{\circ}$ $0^{\circ}$ $15^{\circ}$ $0^{\circ}$ $15^{\circ}$ $15^{\circ}$ $0^{\circ}$ $15^{\circ}$ 15

## Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT

Index 0E1XLL-SLED Name X-LINE Clamp for line luminaires




Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 18-06-2025