

Product: X-LINE LED 4400 MICRO-PRM E 24 840 LINE-S / L-1122MM Index: 19.4169.2221.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information

	Category	Surface mounted luminaires
	Family	X-LINE LED LINE
	Name	X-LINE LED 4400 MICRO-PRM E 24 840 LINE-S / L-1122MM
	Index	19.4169.2221.24
	EAN	5902023880759
		$\underbrace{}_{\operatorname{LED}} \underbrace{}_{\operatorname{ED}} _{\operatorname{ED}} \underbrace{}_{\operatorname{ED}} _{\operatorname{ED}} _{\operatorname$

Light and electrical data

Light source	LED
Luminous flux LED [lm]	4565
LED power [W]	23,4
Luminaire luminous flux [lm]	3438
Power of luminaire [W]	24,7
Luminaire's light efficiency [lm/W]	139,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16)




Mechanical data	Птн	Assembly	directly mounted to ceiling construction or surface mounted on slings
Α	 H ++ B	Material	aluminum
	U	Color	anodised aluminum
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Weight [kg]	2,78
		Dimensions [mm]	1122 x 63 x 74
			90° 75° 60° 45° 45° 300 45° 400 400 400 400 400 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15° 15° 15° 15° 15° 15° 15° 15

Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

