

Product: X-LINE LED 8800 MICRO-PRM EDD 24 840 LINE-1EL / L-2247MM Index: 19.4170.5223.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information	Cat	egory Surface n	nounted lumir	naires		
	Far	nily X-LINE LE				
	Nar	ne X-LINE LE	ED 8800 MICR	O-PRM EDD 24	840 LINE-1EL	/ L-2247MM
	Ind	x 19.4170.5	223.24			
					$[P_{44}] [K_{04}]$	Indoor
Light and electrical data	Ligl	t source		LED		
Light and electrical data		t source inous flux LED [I	m]	LED 9130		
Light and electrical data	Lur		m]			
Light and electrical data	Lur	inous flux LED [l	-	9130		
Light and electrical data	Lur LEC Lur	inous flux LED [l power [W]	flux [lm]	9130 46,8		
Light and electrical data	Lur LEI Lun Pov	inous flux LED [l power [W] inaire luminous f	flux [lm] V]	9130 46,8 6877		

Luminaire luminous flux [lm]	6877
Power of luminaire [W]	49,1
_uminaire's light efficiency [lm/W]	140,1
color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
/oltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)



Mechanical data		Assembly	directly mounted to ceiling construction or surface mounted on slings
A	H B B	Material	aluminum
	D	Color	anodised aluminum
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Weight [kg]	5,2
		Dimensions [mm]	2247 x 63 x 74
			90° 90° 90° 90° 75° 90° 75° 90° 9

Accessories











Index 0E1XLL-SLED
Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 18-06-2025