

Product: X-LINE LED 6600 MICRO-PRM EDD 24 840 LINE-1EP / L-1687MM Index: 19.4171.4223.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information	
---------------------	--

Light and electrical data

	Family	X-LINE LED LINE							
	Name	X-LINE LED 6600 MICRO-PRM EDD 24 840 LINE-1EP / L-1687MM							
	Index	19.4171.4223.24	4						
		CE	LED	E		P ₄₄	IK ₄	Indoor	
	Light sour	rce		L	.ED				
	Luminous	flux LED [lm]		6	848				
	LED powe	er [W]		3	3,7				
	Luminaire	e luminous flux [lm	1]	5	158				
	Power of	luminaire [W]		3	5,3				
	Luminaire	e's light efficiency	[lm/W]	1	46,1				
	Color of the	he light [K]		4	000				
	CRI			>	80				
	SDCM (LI	ED sources)		3					
	Beam ang	gle [°]		((C0-C18	0) / (C90)-C270)	- 82,8°	/ 97,2°

(C16)

Category Surface mounted luminaires




Mechanical data	Птн	Assembly	directly mounted to ceiling construction or surface mounted on slings
Α	L_]H ⊨⊷i B	Material	aluminum
l ₄ }		Color	anodised aluminum
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1687 x 63 x 74
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 60° 45° 60° 45° 60° 45° 45° 45° 45° 45° 45° 45° 45

Accessories












Index 0E1XLL-SLED
Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 18-06-2025