

Product: X-LINE LED 4400 PLX EDD 24 830 LINE-1EP / L-1127MM

Index: 19.4171.2113.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information

| Category | Surface mounted luminaires |
|----------|--|
| Family | X-LINE LED LINE |
| Name | X-LINE LED 4400 PLX EDD 24 830 LINE-1EP / L-1127MM |
| Index | 19.4171.2113.24 |
| EAN | 5902107074876 |
















Light and electrical data

| Light source | LED | |
|--|---|--|
| Luminous flux LED [lm] | 4406 | |
| LED power [W] | 23,4 | |
| Luminaire luminous flux [lm] | 2937 | |
| Power of luminaire [W] | 24,7 | |
| Luminaire's light efficiency [lm/W] | 118,9 | |
| Color of the light [K] | 3000 | |
| CRI | >80 | |
| SDCM (LED sources) | 3 | |
| Beam angle [°] | (C0-C180) / (C90-C270) - 109° / 107,2° | |
| Photobiological risk class (IEC/EN 62471) | RG0 | |
| Protection against electric shock | I | |
| 1 Totodion against cicothe shook | I | |
| Protection degree | IP44 | |
| | • | |
| Protection degree | IP44 | |
| Protection degree Voltage | IP44 220240 V, 5060 Hz | |
| Protection degree Voltage Lifetime of LED sources [h] | IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2) | |
| Protection degree Voltage Lifetime of LED sources [h] Lx/By | IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) | |
| Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] | IP44 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 30 | |



| Mechanical data | | Assembly | directly mounted to ceiling construction or surface mounted on slings |
|-----------------|-----|------------------|---|
| Α | L T | Material | aluminum |
| | | Color | anodised aluminum |
| | | Diffuser | PLX (PMMA opal) |
| | | Impact resistant | IK04 |
| | | Dimensions [mm] | 1127 x 63 x 74 |

A graph of light









Accessories


Index 6E1-500KWAN1P-5

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT




Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24
LENGHT 1,5M WITHOUT WIRE 1POINT




Index 0E1XLL-SLED

Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT

