

Product: X-LINE G/K LED 6600 MICRO-PRM EDD 24 830 LINE-1S / CONNECTOR TYPE-TC 600/600/600

Index: 19.4174.4313.24



Description

The group of X-line luminaries is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaries may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.

Product information

Category Recessed luminaires		
Family	X-LINE G/K LED CONNECTOR T	
Name	X-LINE G/K LED 6600 MICRO-PRM EDD 24 830 LINE-1S / CONNECTOR TYPE-TC 600/600/600	
Index	19.4174.4313.24	
EAN	5902107103019	
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	6608
LED power [W]	33,7
Luminaire luminous flux [lm]	4977
Power of luminaire [W]	35,3
Luminaire's light efficiency [lm/W]	141
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)


Mechanical data



Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1126 x 603 x 134
Mounting hole [mm]	1126 x 598 x 70



A graph of light



Accessories

Index 0E1XLL-SLED

Name X-LINE Clamp for line luminaires

