

Product: X-LINE LED 3900 MICRO-PRM E 24 840 LINE-S / CONNECTOR TYPE-TB 600/600/600 Index: 19.4177.2221.24



Description


Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

| Product information | Category Surface mount | ted luminaires | |
|---------------------------|------------------------------|---|--|
| | Family X-LINE LED CO | DNNECTOR T | |
| | | Name X-LINE LED 3900 MICRO-PRM E 24 840 LINE-S / CONNECTOR TYPE-TB 600/600/600 | |
| | Index 19.4177.2221.2 | 24 | |
| | CE | | |
| Light and electrical data | Light source | LED | |
| | Luminous flux LED [Im] | 3926 | |
| | LED power [W] | 20 | |
| | Luminaire luminous flux [li | m] 2957 | |
| | Power of luminaire [W] | 21,7 | |
| | Luminaire's light efficiency | / [lm/W] 136,3 | |
| | Color of the light [K] | 4000 | |
| | CRI | >80 | |
| | SDCM (LED sources) | 3 | |
| | Beam angle [°] | (C0-C180) / (C90-C270) - 82,8° / 97,2° | |
| | Protection against electric | shock I | |
| | Protection degree | IP44 | |
| | Voltage | 220240 V, 5060 Hz | |
| | Lifetime of LED sources [h | 100000 (1) / 147000 (2) | |
| | Lx/By | L80/B10 (1) / L70/B50 (2) | |
| | Operating temperature rat | nge [°C] 5 ÷ 30 | |
| | Driver | standard on/off (E) | |
| | Power factor $\cos \phi$ | >0,95 | |
| | Circuit load capacity | 22 (B10), 34 (B16), 33 (C10), 54 (C16) | |
| Mechanical data | Assembly | directly mounted to ceiling construction or surface mounted on slings | |
| | Material | aluminum | |
| | t ∺ Color | anodised aluminum | |
| | Diffuser | Micro-PRM (micro-prismatic diffuser PMMA) | |
| | Impact resistant | IK04 | |
| | Dimensions [mm] | 1126 x 593 x 71 | |

Dimensions [mm]

1126 x 593 x 71

A graph of light





Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT

Index 0E1XLL-SLED Name X-LINE Clamp for line luminaires



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025