

Product: X-LINE SLIM L-DOWN LED 8800 PLX E 04 830 LINE-S / L-2244MM S-1,5M Index: 19.4179.4311.04



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

| Product | inform | ation |
|---------|--------|-------|
| iiouuci | | anon |

| Cat | egory S | Surface m | ounted I | umina | aires | | | | | |
|-----|----------------|--------------------|----------|-------|---------|---------|-----------|-------------|---------|-----|
| Far | nily X | -LINE SL | IM LED L | INE | | | | | | |
| Nai | | -LINE SL 5-1,5M | IM L-DO | WN LE | ED 8800 |) PLX E | 04 830 | LINE-S | / L-224 | 4MM |
| Ind | ex 1 | 9.4179.4 | 311.04 | | | | | | | |
| | | | | LED | E | | IP_{40} | K 04 | Indoor | |

Light and electrical data

| | Light source | LED |
|--|---|---|
| | Luminous flux LED [Im] | 8884 |
| | LED power [W] | 43,6 |
| | Luminaire luminous flux [lm] | 5685,8 |
| | Power of luminaire [W] | 49,5 |
| | Luminaire's light efficiency [lm/W] | 114,9 |
| | Color of the light [K] | 3000 |
| | CRI | >80 |
| | SDCM (LED sources) | 3 |
| | Beam angle [°] | (C0-C180) / (C90-C270) - 96,4° / 90,2° |
| | Photobiological risk class (IEC/EN 62471) | RG0 |
| | Protection against electric shock | 1 |
| | Protection degree | IP40 |
| | Voltage | 220240 V, 5060 Hz |
| | Lifetime of LED sources [h] | 100000 |
| | Lx/By | L80/B10 |
| | Operating temperature range [°C] | 5 ÷ 35 |
| | Driver | standard on/off (E) |
| | Power factor cos φ | >0,95 |
| | Circuit load capacity | 12 (B10), 19 (B16), 20 (C10), 32 (C16) |



| Mechanical data | ∏tH ⊮ | Assembly Material Color Diffuser Impact resistant Dimensions [mm] | surface mounted on slings aluminum RAL 9005 (black) PLX (PMMA opal) IK04 2244 x 48 x 70 |
|------------------|----------|--|---|
| A graph of light | | | $105^{\circ} \qquad 100^{\circ} \qquad 90^{\circ} \qquad$ |
| | | | |

Accessories

Poland

LUXIONA


Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

