

Product: X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 24 830 LINE-EL / L-2252MM S-1,5M Index: 19.4179.4411.24



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product information	
---------------------	--

	Category	Surface mounted luminaires
	Family	X-LINE SLIM LED LINE
	Name	X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 24 830 LINE-EL / L- 2252MM S-1,5M
	Index	19.4179.4411.24

 $\langle E \rangle$

 \mathbb{IP}_{40}

A

E

Light and electrical data

	Light source	LED
	Luminous flux LED [Im]	8884
	LED power [W]	43,6
	Luminaire luminous flux [lm]	6574,2
	Power of luminaire [W]	49,5
	Luminaire's light efficiency [lm/W]	132,8
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	standard on/off (E)
	Power factor cos φ	>0,95
	Circuit load capacity	12 (B10), 19 (B16), 20 (C10), 32 (C16)



Mechanical data	□tH B	Assembly Material Color Diffuser	surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant Dimensions [mm]	IK04 2252 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 90° 60° 200 45° 300 45° 300 45° 300 45° 15° 0° 15° 15° 15°

Accessories

Poland

LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025