

## Product: X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 24 830 LINE-EP / L-2252MM S-1,5M Index: 19.4179.4511.24



## Description

Protection degree

Power factor  $\cos \varphi$ 

Circuit load capacity

Lifetime of LED sources [h]

Operating temperature range [°C]

Voltage

Lx/By

Driver

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuot		anon

Product information		Category Surface mounted luminaires									
		Family	amily X-LINE SLIM LED LINE								
		Name	X-LINE SLIM L-D 2252MM S-1,5M	8800 MICR	CRO-PRM E 24 830 LINE-EP / L-						
		Index	19.4179.4511.24								
			CE			<b>IP</b> <sub>40</sub>	<b>K</b> <sub>04</sub>	Indoor			
Light and electrical data	Ī	Light sour	rce		LED						
	L	<mark>Lum</mark> inous	flux LED [lm]		8884						
	L	LED powe	er [W]		43,6						
	L	Luminaire	e luminous flux [lm]		6574,2						
	F	Power of	luminaire [W]		49,5						
	L	Luminaire	e's light efficiency [li	m/W]	132,8						
	C	Color of th	he light [K]		3000						
	Ċ	CRI			>80						
	9	SDCM (LI	ED sources)		3						
	E	Beam ang	gle [°]		(C0-C18	0) / (C90	)-C270)	- 88,4°	/ 86°		
		Photobiol 62471)	ogical risk class (IE	C/EN	RG0						
	F	Protectior	n against electric sh	nock							

**IP40** 

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

12 (B10), 19 (B16), 20 (C10), 32



Mechanical data	tH Material		surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA)			
		Impact resistant Dimensions [mm]	IK04 2252 x 48 x 70			
A graph of light			105°       105°         90°       90°         75°       90°         60°       200         45°       300         45°       300         45°       300         45°       90°         45°       90°         45°       90°         45°       90°         45°       90°         45°       90°         45°       90°         45°       90°         400       90°         90° <td< th=""></td<>			

# Accessories

Poland


**LUXIONA** 

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025