

Product: X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 34 840 LINE-EP / L-2252MM S-1,5M Index: 19.4179.4521.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

220..240 V, 50..60 Hz

standard on/off (E)

12 (B10), 19 (B16), 20 (C10), 32

100000

L80/B10

5 ÷ 35

>0,95

(C16)

Product	inform	ation
FIUUUUL		αιισπ

Product information	C	Category Surface mounted luminaires			
	F	Family	X-LINE SLIM LED LINE		
		Name X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 34 2252MM S-1,5M		3800 MICRO-PRM E 34 840 LINE-EP / L-	
	li	ndex	19.4179.4521.34		
Light and electrical data	L	Light sou	rce	LED	
	L	Luminou:	s flux LED [lm]	9352	
	L	LED pow	er [W]	43,6	
	L	Luminaire	e luminous flux [lm]	6920,5	
	F	Power of	luminaire [W]	49,5	
	L	Luminair	e's light efficiency [lm/W]	139,8	
	C	Color of t	he light [K]	4000	
	C	CRI		>80	
	5	SDCM (L	ED sources)	3	
	E	Beam an	gle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°	
		Photobio 62471)	logical risk class (IEC/EN	RG0	
	F	Protectio	n against electric shock	I	
		Protectio	n degree	IP40	

Voltage

Lx/By

Driver

Lifetime of LED sources [h]

Power factor $\cos \varphi$

Circuit load capacity

Operating temperature range [°C]



Mechanical data		Assembly	surface mounted on slings
	ЦЦЦН	Material	aluminum
Α	l⊶+l B	Color	RAL 9016 (white)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	2252 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 45° 45° 45




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

