

Product: X-LINE SLIM L-DOWN LED 13200 PLX EDD 24 840 LINE-1S / L-3370MM S-1,5M Index: 19.4179.5323.24



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Ρ	roduct	information
۰.	louuci	mormation

CategorySurface mounted luminairesFamilyX-LINE SLIM LED LINENameX-LINE SLIM L-DOWN LED 13200 PLX EDD 24 840 LINE-1S / L-
3370MM S-1,5MIndex19.4179.5323.24

Œ

LED

 $\mathbb{I}P_{40}$

Light and electrical data

	Light source	LED
	Luminous flux LED [lm]	14028
	LED power [W]	65,4
	Luminaire luminous flux [lm]	8977,9
	Power of luminaire [W]	74,3
	Luminaire's light efficiency [lm/W]	120,8
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	DIM DALI (EDD)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	7 (B10), 11 (B16), 11 (C10), 17 (C16)



Mechanical data	∏tH ⊨+i B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum PLX (PMMA opal) IK04 3370 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 250 250 45° 45° 45° 45° 45° 45° 45° 45° 45° 45°

Poland

LUXIONA

Accessories

Index 6E1-500KWAN1P-5 Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025