

Product: X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 34 830 LINE-EP / L-2252MM S-1,5M Index: 19.4179.5411.34



Description

62471)

Voltage

Lx/By

Driver

Protection degree

Power factor $\cos \phi$

Circuit load capacity

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuot		anon

Product Information		Category Surface mounted luminaires				
		Family	amily X-LINE SLIM LED LINE			
		Name	ame X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 34 830 LINE-EP / L- 2252MM S-1,5M			
		Index	19.4179.5411.34			
				b b b b b b b b	Indoor	
Light and electrical data		Light sou	urce	LED		
		Luminou	is flux LED [lm]	8884		
		LED pov	ver [W]	43,6		
		Luminai	re luminous flux [lm]	6574,2		
		Power of	f luminaire [W]	49,5		
		Luminai	re's light efficiency [lm/W]	132,8		
		Color of	the light [K]	3000		
		CRI		>80		
		SDCM (I	LED sources)	3		
		Beam ar	ngle [°]	(C0-C180) / (C90-C270) -	88,4° / 86°	
		Photobic	ological risk class (IEC/EN	RG0		

I IP40

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

12 (B10), 19 (B16), 20 (C10), 32

Catagory Surface mounted luminaires



Mechanical data		Assembly	surface mounted on slings
	ЦЦЦН	Material	aluminum
Α	l⊶+l B	Color	RAL 9016 (white)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	2252 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 45° 45° 45




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

