

## Product: X-LINE SLIM L-DOWN LED 13200 MICRO-PRM EDD 21 830 LINE-1S / L-3370MM S-1,5M Index: 19.4179.5613.21



#### Description

Power factor  $\cos \phi$ 

Circuit load capacity

Category Surface mounted luminaires

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUUL		αιισπ

Light and electrical data

Family	X-LINE SLIM LED	LINE					
Name	X-LINE SLIM L-DOWN LED 13200 MICRO-PRM EDD 21 830 LINE-1S / L-3370MM S-1,5M						
Index	19.4179.5613.21						
	CE	LED E		<b>IP</b> <sub>40</sub>		Indoor	<b>A</b>
Light sou	rce		LED				
Luminous	s flux LED [lm]		13326				
LED pow	er [W]		65,4				
Luminaire luminous flux [lm]			9861,2				
Power of luminaire [W]			74,3				
Luminaire's light efficiency [lm/W]		132,7					
Color of the light [K]			3000				
CRI			>80				
SDCM (L	ED sources)		3				
Beam angle [°]			(C0-C180) / (C90-C270) - 88,4° / 86°				
Photobiological risk class (IEC/EN 62471)		C/EN	RG0				
Protection against electric shock		lock	I				
Protection degree		IP40					
Voltage		220240 V, 5060 Hz					
Lifetime of LED sources [h]			100000				
Lx/By			L80/B10				
Operating temperature range [°C]			5 ÷ 35				
Driver			DIM DALI (EDD)				

>0,95

(C16)

14 (B10), 23 (B16), 22 (C10), 35



Mechanical data	⊟H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9006 (grey) Micro-PRM (micro-prismatic diffuser PMMA) IK04 3370 x 48 x 70
A graph of light			105°       105°         90°       90°         75°       90°         60°       200         45°       60°         45°       300         30°       15°         30°       15°         90°       90°         90°       15°

## -----

Poland

**LUXIONA** 

### Accessories

# Index 6E1-500KWAN1P-5 Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



#### Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025