

Product: X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 34 830 LINE-S / L-2244MM S-1,5M Index: 19.4179.6411.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	alion

Category	Surface mounted luminaires
Family	X-LINE SLIM LED LINE
Name	X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 34 830 LINE-S / L- 2244MM S-1,5M
Index	19.4179.6411.34
	$\underbrace{ED} \bigoplus \bigoplus \underbrace{P}_{40} \bigoplus \underbrace{P}_{40} \bigoplus \underbrace{P}_{100} \bigoplus \underbrace{P}_{1000} \bigoplus \underbrace{P}_{1000} \bigoplus \underbrace{P}_{10000} \bigoplus \underbrace{P}_{100000} \bigoplus \underbrace{P}_{1000000} \bigoplus \underbrace{P}_{1000000} \bigoplus \underbrace{P}_{1000000} \bigoplus \underbrace{P}_{1000000} \bigoplus \underbrace{P}_{10000000} \bigoplus \underbrace{P}_{100000000} \bigoplus \underbrace{P}_{1000000000} \bigoplus \underbrace{P}_{100000000} \bigoplus \underbrace{P}_{1000000000} \bigoplus \underbrace{P}_{10000000000} \bigoplus \underbrace{P}_{100000000000} \bigoplus \underbrace{P}_{1000000000000000000000000} \bigoplus \underbrace{P}_{100000000000000000000000000000000000$

Light and electrical data

	Light source	LED
	Luminous flux LED [lm]	8884
	LED power [W]	43,6
	Luminaire luminous flux [lm]	6574,2
	Power of luminaire [W]	49,5
	Luminaire's light efficiency [lm/W]	132,8
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	standard on/off (E)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	12 (B10), 19 (B16), 20 (C10), 32 (C16)



Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) Micro-PRM (micro-prismatic diffuser PMMA) IK04 2244 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 90° 60° 200 45° 300 45° 45° 30° 15° 30° 15° 0° 0° 400 30° 15° 30° r = 74%




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

