

Product: X-LINE SLIM L-DOWN LED 2200 PLX EDD 24 840 LINE-1EL / L-572MM S-1,5M Index: 19.4179.1123.24



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	auon

Category	Surface mounted luminaires				
Family	X-LINE SLIM LED LINE				
Name	X-LINE SLIM L-DOWN LED 2200 PLX EDD 24 840 LINE-1EL / L- 572MM S-1,5M				
Index	19.4179.1123.24				
	$\underbrace{}_{\text{LED}} \underbrace{}_{\text{E}} \underbrace{}_{\text{E}} \underbrace{}_{\text{Hoor}} \underbrace{\end{array}{}_{\text{Hoor}} \underbrace{}_{\text{Hoor}} \underbrace{\end{array}{}_{\text{Hoor}} _{\text{Hoor}} \underbrace{\end{array}{}_{\text{Hoor}} \underbrace{\end{array}{}_{\text{Hoor}} \underbrace{\end{array}{}_{\text{Hoor}} _{\text{Hoor}} _{$				

Light and electrical data

Light source	LED
Luminous flux LED [lm]	2338
LED power [W]	10,9
Luminaire luminous flux [lm]	1496,3
Power of luminaire [W]	12,8
Luminaire's light efficiency [lm/W]	116,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	14 (B10), 24 (B16), 22 (C10), 36 (C16)



Mechanical data	⊟‡H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum PLX (PMMA opal) IK04 572 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 200 45° 45° 45° 45° 45° 45° 45° 45° 45° 45°

Poland

LUXIONA

Accessories

Index 6E1-500KWAN1P-5 Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025