

## Product: X-LINE SLIM L-DOWN LED 2200 PLX E 21 830 LINE-S / L-564MM S-1,5M Index: 19.4179.1311.21



### Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUUL		αιισπ

Light and electrical data

Family	ily X-LINE SLIM LED LINE							
Name	X-LINE SLIM L 1,5M	-DOWN LE	ED 2200 P	PLXE	21 830	LINE-S	6 / L-564	IMM S-
Index	19.4179.1311.2	21						
	Ce	LED			<b>IP</b> <sub>40</sub>	<b>K</b> <sub>04</sub>	Indoor	
Light sou	rce		LED	)				
Luminous	s flux LED [lm]		2221	1				
LED pow	er [W]		10,9	)				
Luminair	e luminous flux [l	m]	1421	1,4				
Power of	luminaire [W]		12,8	;				
Luminaire's light efficiency [lm/W]		111						
Color of the light [K]		3000	D					
CRI			>80					
SDCM (LED sources)		3						
Beam angle [°]		(C0-	C180)	/ (C90	-C270)	- 96,4°	/ <b>90,2</b> °	
Photobiological risk class (IEC/EN 62471)		RG0	)					
Protection against electric shock		I						
Protection degree		IP40	)					
Voltage		220.	.240 V	, 506	0 Hz			
Lifetime of LED sources [h]		1000	000					
Lx/By			L80/	/B10				
Operating temperature range [°C]		5 ÷ 3	35					
Driver		stan	ndard o	on/off	(E)			
Power factor $\cos \phi$		>0,9	5					

46 (B10), 74 (B16), 72 (C10), 115

(C16)

Category Surface mounted luminaires

Circuit load capacity



Mechanical data	H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9006 (grey) PLX (PMMA opal) IK04 564 x 48 x 70
A graph of light			105°       105°         90°       90°         75°       90°         60°       100         60°       100         45°       200         45°       200         300       15°         300       15°         300       15°         300       15°         45°       30°         45°       30°         45°       30°         45°       30°         45°       30°         45°       30°         45°       30°         45°       30°         45°       30°         45°       45°         45°       30°         50°       15°         60°       45°         75°       30°

# Accessories

Poland


**LUXIONA** 

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025