


### Product: X-LINE SLIM L-DOWN LED 2200 PLX E 34 830 LINE-S / L-564MM S-1,5M Index: 19.4179.1311.34



## Description

Category Surface mounted luminaires

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUUL		αιισπ

Light and electrical data

	Family X-LINE SLIM LED LINE									
	Name	X-LINE SLIM L-DOWN LED 2200 PLX E 34 830 LINE-S / L-564MM S- 1,5M				IMM S-				
	Index	19.4179.1	311.34							
			Œ	LED	E		<b>IP</b> <sub>40</sub>	<b>K</b> <sub>04</sub>	Indoor	
	Light sou	irce			L	.ED				
	Luminou	s flux LED [l	m]		2	2221				
	LED pow	er [W]			1	.0,9				
	Luminaire luminous flux [lm]				1	1421,4				
	Power of luminaire [W]				1	12,8				
	Luminaire's light efficiency [lm/W]				1	111				
	Color of the light [K]				3	3000				
	CRI				>	•80				
	SDCM (LED sources)				3	3				
	Beam an	gle [°]			(	C0-C180	) / (C90	)-C270)	- 96,4°	/ 90,2°
	Photobiological risk class (IEC/EN 62471)		F	RG0						
	Protection against electric shock		I							
	Protection degree		I	IP40						
	Voltage		2	220240 V, 5060 Hz						
	Lifetime of LED sources [h]		1	100000						
	Lx/By				L	.80/B10				
	Operating temperature range [°C]		5	5 ÷ 35						
	Driver		s	standard on/off (E)						
Power factor $\cos \phi$		>	•0,95							
Circuit load capacity			4	46 (B10), 74 (B16), 72 (C10), 115						

(C16)



Mechanical data	H B B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slingsaluminumRAL 9016 (white)PLX (PMMA opal)IK04564 x 48 x 70
A graph of light			$\int_{0}^{105^{\circ}} \int_{0}^{10^{\circ}} \int_{$




# Accessories

#### Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

