

Product: X-LINE SLIM L-DOWN LED 2200 PLX E 24 840 LINE-S / L-564MM S-1,5M Index: 19.4179.1321.24



Description

Power factor $\cos \phi$

Circuit load capacity

Category Surface mounted luminaires

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation

Light and electrical data

	Family	X-LINE SLIM LED L	.INE					
	Name	X-LINE SLIM L-DO 1,5M	WN LED 220	00 PLX E	24 840	LINE-S	/ L-564	MM S-
	Index	19.4179.1321.24						
					IP ₄₀	K ₀₄	Indoor	
	Light sou	rce	I	ED				
	Luminous	s flux LED [lm]	2	2338				
	LED power [W]		1	10,9				
	Luminaire luminous flux [lm]		1	496,3				
	Power of luminaire [W]		1	L2,8				
	Luminaire's light efficiency [lm/W]		W] 1	16,9				
	Color of the light [K]		4	1000				
	CRI		>	>80				
	SDCM (L	ED sources)		3				
	Beam angle [°]			(C0-C180) / (C90-C270) - 96,4° / 90,2°				
	Photobiological risk class (IEC/EN 62471)		EN I	RG0				
	Protection against electric shock		ck I					
	Protection degree		I	IP40				
	Voltage		2	220240 V, 5060 Hz				
	Lifetime of LED sources [h]		1	100000				
Lx/By		I	.80/B10					
	Operating temperature range [°C] Driver		[°C] !	5 ÷ 35				
			9	standard	on/off	(E)		

>0,95

(C16)

46 (B10), 74 (B16), 72 (C10), 115



Mechanical data	⊟tH B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum anodised aluminum PLX (PMMA opal) IK04 0,93 564 x 48 x 70
A graph of light			

Accessories

Poland

LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025