

Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 830 LINE-EL / L-572MM S-1,5M Index: 19.4179.1411.21



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	alion

Product information	Category Surface mounted luminaires		
	Family	X-LINE SLIM LED LINE	
	Name	X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 83 572MM S-1,5M	30 LINE-EL / L-
	Index	19.4179.1411.21	
		$\underbrace{E}_{LED} \underbrace{E}_{ED} \underbrace{E}_{$	Indoor
Light and electrical data	Light so	urce LED	
	Luminou	us flux LED [lm] 2221	
		wer [W] 10,9	
	Luminai	re luminous flux [lm] 1643,5	
		of luminaire [W] 12,8	
	Luminai	re's light efficiency [lm/W] 128,4	
	Color of	the light [K] 3000	

Luminaire's ligh	efficiency [lm/W] 128	3,4
Color of the ligh	[K] 300	00
CRI	>80)
SDCM (LED sou	rces) 3	
Beam angle [°]	(C0	-C180) / (C90-C270) - 88,4° / 86°
Photobiological 62471)	isk class (IEC/EN RG	0
Protection agair	st electric shock	
Protection degr	e IP4	0
Voltage	220)240 V, 5060 Hz
Lifetime of LED	ources [h] 100	0000
Lx/By	L80)/B10
Operating temp	rature range [°C] 5 ÷	35
Driver	sta	ndard on/off (E)
Power factor co	φ >0,9	95
Circuit load cap	city 46	(B10), 74 (B16), 72 (C10), 115

(C16)



Mechanical data	H B B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9006 (grey) Micro-PRM (micro-prismatic diffuser PMMA) IK04 572 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 90° 60° 200 60° 60° 45° 60° 30° 15° 30° 15° 0° 15° 0° 15° 15° 0° 15° 0° 15° 0° 15° 15°

Accessories

Poland


LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025