

## Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 24 840 LINE-EL / L-572MM S-1,5M Index: 19.4179.1421.24



## Description

62471)

Voltage

Lx/By

Driver

Protection degree

Power factor  $\cos \phi$ 

Circuit load capacity

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuot		anon

Product information	Category	Category       Surface mounted luminaires         Family       X-LINE SLIM LED LINE         Name       X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 24 840 LINE-EL / L- 572MM S-1,5M         Index       19.4179.1421.24	
	Family		
	Name		
	Index		
Light and electrical data	Light sou	irce	LED
	Luminou	s flux LED [lm]	2338
	LED pow	ver [W]	10,9
	Luminair	e luminous flux [lm]	1730,1
	Power of	luminaire [W]	12,8
	Luminair	e's light efficiency [lm/W]	135,2
	Color of	the light [K]	4000
	CRI		>80
	SDCM (L	ED sources)	3
	Beam an	ngle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobio	logical risk class (IEC/EN	RG0

L

IP40

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

46 (B10), 74 (B16), 72 (C10), 115



Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA) IK04 572 x 48 x 70
A graph of light			105°       105°         90°       90°         75°       90°         60°       200         45°       60°         45°       300         45°       400         30°       15°         30°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°

# Accessories

Poland


**LUXIONA** 

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025