

## Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 24 840 LINE-EP / L-572MM S-1,5M Index: 19.4179.1521.24



### Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	information	
FIGUUCI	mormation	

Light and electrical data

	Category	Surface mounted luminal	res	
	Family	X-LINE SLIM LED LINE		
	Name	X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 24 840 LINE-EP / L- 572MM S-1,5M		
	Index	19.4179.1521.24		
	Light sou	irce	LED	
	Luminous flux LED [Im] LED power [W] Luminaire luminous flux [Im] Power of luminaire [W] Luminaire's light efficiency [Im/W]		2338	
			10,9	
			1730,1	
			12,8	
			135,2	
	Color of	the light [K]	4000	
	CRI		>80	

3

L

RG0

IP40

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

46 (B10), 74 (B16), 72 (C10), 115

(C0-C180) / (C90-C270) - 88,4° / 86°

Catagory Surface mounted luminaires

SDCM (LED sources)

Photobiological risk class (IEC/EN

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

Beam angle [°]

Protection degree

Power factor  $\cos \phi$ 

Circuit load capacity

62471)

Voltage

Lx/By

Driver



Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA) IK04 572 x 48 x 70
A graph of light			105°       105°         90°       90°         75°       90°         60°       200         45°       60°         45°       300         45°       400         30°       15°         30°       15°         0°       15°         0°       15°         15°       30°

# Accessories

Poland


**LUXIONA** 

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025