

Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 840 LINE-EP / L-572MM S-1,5M Index: 19.4179.1521.21



Description

62471)

Voltage

Lx/By

Driver

Protection degree

Power factor $\cos \varphi$

Circuit load capacity

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

| Product | inform | ation |
|---------|--------|-------|
| FIUUUCI | | auon |

Light and electrical data

| | Cuicgory | Surface mounte | u iuiiiii | anco | | | | | |
|---------------|-------------------------------------|---|-----------|------|--------------------------------------|-------------------------|------------------------|--------|--|
| | Family | X-LINE SLIM LED LINE | | | | | | | |
| | Name | X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 840 LINE-EP / L- 572MM S-1,5M | | | | | | | |
| | Index | 19.4179.1521.21 | | | | | | | |
| | | CE | LED | E | | IP ₄₀ | K ₀₄ | Indoor | |
| | Light sou | rce | | L | ED | | | | |
| | | s flux LED [lm] | | | 338 | | | | |
| | | | | | | | | | |
| LED power [W] | | | | 0,9 | | | | | |
| | Luminair | e luminous flux [lm] | | 17 | 730,1 | | | | |
| | Power of | luminaire [W] | | 12 | 2,8 | | | | |
| | Luminaire's light efficiency [lm/W] | | | 1: | 35,2 | | | | |
| | Color of the light [K] | | | 4(| 000 | | | | |
| | CRI | | | > | 80 | | | | |
| | SDCM (LED sources) | | | 3 | | | | | |
| | Beam angle [°] | | | (0 | (C0-C180) / (C90-C270) - 88,4° / 86° | | | | |
| | Photobiological risk class (IEC/EN | | | R | G0 | | | | |

I

IP40

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

46 (B10), 74 (B16), 72 (C10), 115

Category Surface mounted luminaires



| Mechanical data | H B B | Assembly Material Color Diffuser Impact resistant Dimensions [mm] | surface mounted on slings aluminum RAL 9006 (grey) Micro-PRM (micro-prismatic diffuser PMMA) IK04 572 x 48 x 70 |
|------------------|-------------|--|--|
| A graph of light | | | 105° 105° 90° 90° 75° 90° 60° 200 60° 60° 45° 60° 30° 15° 30° 15° 0° 15° 0° 15° 15° 0° 15° 0° 15° 0° 15° 15° |
| | | | |

Accessories

Poland


LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025